



## FBT - PROMAXX110A ACTIVE SPEAKER 10in 700W + 200W

SKU: 406.050FB

With a specially developed polypropylene cabinet and stylish full grille aesthetic, the new PROMAXX by FBT represents the next step in the evolution of a portable sound classic. Equipped with custom FBT speakers complete with B&C's renowned compression driver technology, PROMAXX combines true made-in-Italy quality and style. At its heart is a purpose-built FBT amplifier module with a switch-mode power supply. For the low frequency section, 700W RMS is driven via a highly efficient Class-D topology, boasting extremely low THD. For HF,...

### Details

Categories: Point Source Speakers, Portable Event Speakers, SPEAKERS

### Features & Specifications

#### Features:

- 2-way, bi-amplified, bass reflex design cabinet
- Biamped: 700W RMS LF, 200W RMS HF, power amplifiers in Class D for LF and in Class H/AB for HF with switch mode power supplies
- Digital signal processor with graphic display
- Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push
- 2 x M10 suspension points, 35 mm (1,3/8") top-hat speaker stand socket, wall bracket mount flange plate
- 90°H x 60°V constant directivity horn
- Front of House or Stage Floor Monitor: with 12°, 40° and 55° monitoring angles

#### Specifications:

- Power cord: 5m
- Net Dimension (WxHxD): 320 x 550 x 275mm
- Net Weight: 10.3kg
- Transport Dimension (WxHxD): 400 x 630 x 360mm
- Transport Weight: 12.8kg
- Configuration: 2 Way
- Built in amplifier: 900w (700w LF + 200w HF)
- Built in amplifier peak: 1800w (1400w LF + 400w HF)
- Frequency Response: 58Hz - 20kHz -6dB
- Low Frequency Woofer: 10
- High Frequency driver: 1
- Maximum SPL continuous/peak: 124/131dB
- Dispersion (HxV): 90x 60
- Input Impedance: 22kOhm
- AC power requirements: 640VA
- Input Connector: XLR/Jack Combo socket with XLR link out, RCA stereo input